Driver Vehicle Inspection Report

Have all defects corrected before departure.

- 1. Approaching vehicle note general condition. Look for leakage of water, fuel, or lubricants under vehicle.
- 2. Under the hood, check water and crankcase levels. Check fan and compressor belts for cracks and excessive slack and wear. Note general condition of engine space.
- 3. Start engine and set at fast idle for warm-up. Check for abnormal engine noise. Check gauges for normal readings (pilot lights, if equipped). "LOW AIR" warning should operate if air pressure is below 60 pounds. Anti-lock warning light should light briefly and then go out (vehicles with 121 air brakes and operable anti-lock).
- 4. Check emergency equipment, horn(s), windshield wipers. Turn on all lights including 4-way flasher switch for turn signals. Check steering wheel action.
- 5. Leave cab to check headlights and turn signals. Switch headlights on and check both beams, then turn off headlights only. Leave all other lights on.
- 6. Check front clearance and identification lights.
- 7. Check left and right front wheels, tires, lugs or studs. Check for leaks around hubs.
- 8. Check right side of cab, door, mirrors, etc. and check lights and reflectors along right side as inspection progresses.
- 9. Check right rear tractor tires, wheels, lugs or studs. Note any thrown lubricant.
- 10. Check trailer light and brake lines for secure connections. Be sure manual petcocks are open. Be sure lines are properly secured to prevent entangling or chafing.
- 11. Check hook-up: fifth-wheel, jaws, release lever on tractor-trailer; pintle hook, tow bar, safety chains, converter gear on full-trailer unit.
- 12. Check right trailer tires, wheels, lugs or studs. Check for thrown lubricant.
- 13. Check rear of body, mud flaps, rear lights (clearance and identification, stop, tail, turn signals), rear reflectors, rear end protection.
- 14. Check left trailer tires, wheels, lugs or studs. Check lights and reflectors on left side as inspection progresses.
- 15. Check left rear tractor tires, wheels, lugs or studs. Check for thrown lubricant.
- 16. Re-enter cab. Re-check all gauges. Air pressure should be at maximum.
- 17. Check parking brake.

HOS - Hours of Service

- 18. Check brakes and stoplights. With fully charged system, check air brakes as follows:
 - a. Older tractors (pre-121 brakes):
 - i. Put trailer air supply valve in "Normal". Use treadle valve to apply and release brakes.
 - ii. Release treadle valve and put trailer air supply valve in "Emergency". Trailer brakes should come on and stay on. Return trailer air supply valve to "Normal" and fan down brakes. Re-check for activation of "Low Air" warning at 60 psi. Between 45 and 20 psi, the trailer brakes should come on.
 - b. New tractors (equipped with 121 brakes): WARNING Because many of the following checks must be performed with parking brake(s) released, driver must remain in vehicle ready to re-apply parking brake(s) if necessary.
 - i. Release all parking brakes.
 - ii. Push trailer air supply valve to "Supply". Use treadle valve to apply and release brakes.
 - iii. Release treadle valve. Place tractor park valve in "Park". Tractor brakes, only, should apply.
 - iv. Apply tractor-trailer park valve. Trailer brakes should apply.
 - v. Release all parking brakes and turn off engine. Use treadle valve to fan down brakes. At 60 psi on primary reservoir, "Low Air" warning should operate and pressure in secondary reservoir should start to drop. Between 45 and 20 psi in secondary reservoir, all brakes should apply.
 - c. All tractors:
 - i. Recharge system to check for leaks.
 - ii. Apply service brakes and hold for 1 minute with engine idling. After initial pressure drop of 5-10 psi, pressure drop should not exceed 4 psi.
 - iii. If audible leaks or rapid pressure drop are noted, have leakage corrected before departure.
- 19. Turn off 4-way flasher and actuate left and right turn signals. Proper operation of turn signals can be ascertained by checking front ones.
- 20. Make a test stop before leaving yard. Drain air tanks daily. Check tires twice daily or every 100 miles.
- 21. Use the DVIR form to report vehicle condition at end of run.

Sample: Driver's Vehicle Inspection Report			
Check defects only. Explain under Remarks. Completion of this report required by FMCSR 49 CFR 396.11 and 396.13.			
Tractor Number or License Plate Number	Vehicle Make	Total Miles Loc	cation
Della March en	Toda Noveles and Linear Dieta Noveles	Tatal Harris Tio	
Dolly Number	Trailer Number or License Plate Number	Total Hours Tin	ne
Code numbers for maintenance department use only.			
	Power Unit		
General Condition	In-Cab	Exterior	☐ NO DEFECTS
02 Cab/Doors/Windows	03 Gauges/Warning Indicators	34 Lights	
02 Body/Doors	Brake Air Pressure or Vacuum Gauge	34 Reflectors	
Oil Leak	Brake Failure Warning Light	16 Suspension	
Grease Leak	Low Pressure Warning Signal	17 Tires	
42 Coolant Leak	02 Windshield Wipers/Washers	18 Wheels/Rims/Lugs	
44 Fuel Leak	54 Horn(s)	32 Battery	
Air Brake Adjustment	01 Heater/Defroster	43 Exhaust	
Drive Line	02 Mirrors	13 Brakes	
Other	15 Steering	13 Air Lines	
	23 Clutch	34 Light Line	
(Identify)	13 Service Brakes	49 Fifth-Wheel	
Engine Compartment	13 Parking Brake	49 Other Coupling	
45 Oil Level	13 Emergency Brakes	71 Tie-Downs	
42 Coolant Level	53 Reflective Triangles	☐ 14 Rear End Protection	
Belts	53 Fire Extinguisher	Load Covering	
Air Compressor	Other Safety Equipment	Load Security/Tie-Downs	
Air Line Connections	34 Spare Fuses	55 Power Liftgate	
Other	02 Seat Belts	Other	
	99 Spill Kit		
(Identify)	Regristration/Permits	(Identify)	
Towed Unit(s)			
	_		☐ NO DEFECTS
71 Body/Doors 16 Suspension	77 Landing Gear	79 Rear-End Protection	
71 Tie-Downs 17 Tires	59 Kingpin/Upper Plate	55 Power Liftgate	
34 Lights 18 Wheels/Rims/Lu		Other	<u> </u>
34 Reflectors 13 Brakes	59 Other Coupling Devices	(Identify)	
Remarks			
Reporting Driver	Date	Maintenance Action Date	
Signature	Employee Number	Repairs Made	
Reviewing Driver	Date	Certified By	
Signature	Employee Number Location		
Maintenance Department Remarks			